





www.pyroguard.co.za

www.deleifire.com

GASES DATA SHEET: NITROGEN GENERAL INDUSTRIAL DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION	
Product Name	Nitrogen
Chemical formula	N_2
Synonyms	Nitrogen, Nitrogen gas, Gaseous Nitrogen, GAN
Use of the substance/preparation	General Industrial
Manufacturer/Importer/Distributor	Air Products South Africa (Pty) Ltd. 4 Spencer Rd, Spartan Ext.1, Kempton Park, 1620
Telephone	+27 (0)11 570 5000 (Head Office) +27 (0)11 977 6444 (Customer Care Cylinders) 0800 023 298 (Engineering / Bulk Services)
Emergency telephone Number (24h)	0800 650 315

2. COMPOSITION / INFORMATION ON INGREDIENTS

Components	CAS Number	Concentration (Volume)
Nitrogen	7727-37-9	100 %

Concentration is nominal. For the exact product composition, please refer to Air Products technical specifications.

3. HAZARDS IDENTIFICATION

Main Hazard / Emergency Overview

High pressure gas.

Simple asphyxiant - Can cause rapid suffocation.

Self contained breathing apparatus (SCBA) may be required.

Potential Health Effects		
Inhalation	In high concentrations may cause asphyxiation. Asphyxiation may bring about unconsciousness without warning and so rapidly that victim may be unable to protect themselves.	
Eye contact	No adverse effect.	
Skin contact	No adverse effect.	
Ingestion	Ingestion is not considered a potential route of exposure.	
Chronic Health Hazard	Not applicable.	
Aggravated Medical Condition	None.	
Symptoms	Exposure to oxygen deficient atmosphere may cause the following symptoms: Dizziness. Salivation. Nausea. Vomiting. Loss of mobility/consciousness.	
Environmental Effects		
Not harmful.		
4. FIRST AID MEASURES		
General advice	Remove victim to uncontaminated area wearing self contained breathing apparatus. Kee victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.	
Eye contact	Not applicable.	
Skin contact	Not applicable.	
Ingestion	Ingestion is not considered a potential route of exposure.	
Inhalation	Remove to fresh air. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately. In case of shortness of breath, give oxygen.	





www.pyroguard.co.za

www.deleifire.com

GASES DATA SHEET: NITROGEN GENERAL INDUSTRIAL DATA SHEET

Suitable extinguishing media	All known extinguishing media can be used.
Specific hazards	Upon exposure to intense heat or flame, cylinder will vent rapidly and or rupture violently. Product is nonflammable and does not support combustion. Move away from container and cool with water from a protected position. Keep containers and surroundings cool with water spray.
Special protective equipment for fire- fighters	Wear self contained breathing apparatus for fire fighting if necessary.
6. ACCIDENTAL RELEASE MEASU	RES
Personal precautions	Evacuate personnel to safe areas. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Monitor oxygen level. Ventilate the area.
Environmental precautions	Do not discharge into any place where its accumulation could be dangerous. Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Ventilate the area.
Additional advice	If possible, stop flow of product. Increase ventilation to the release area and monitor oxygen level. If leak is from cylinder or cylinder valve, call the Air Products emergency telephone number. If the leak is in the user's system, close the cylinder valve, safely vent the pressure, and purge with an inert gas before attempting repairs.
7. HANDLING AND STORAGE	

Handling

Protect cylinders from physical damage; do not drag, roll, slide or drop. Do not allow storage area temperature to exceed 50°C. Only experienced and properly instructed persons should handle compressed gases. Before using the product, determine its identity by reading the label. Know and understand the properties and hazards of the product before use. When doubt exists as to the correct handling procedure for a particular gas, contact the supplier. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Do not remove valve guards. Before connecting the container, check the complete gas system for suitability, particularly for pressure rating and materials. Before connecting the container for use, ensure that back feed from the system into the container is prevented. Ensure the complete gas system is compatible for pressure rating and materials of construction. Ensure the complete gas system has been checked for leaks before use. Employ suitable pressure regulating devices on all containers when the gas is being emitted to systems with lower pressure rating than that of the container.

Open valve slowly. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Close valve after each use and when empty. Do not subject containers to abnormal mechanical shocks which may cause damage to their valve or safety devices. Never attempt to lift a cylinder by its valve guard. Do not use containers as rollers or supports or for any other purpose than to contain the gas as supplied. Never strike an arc on a compressed gas cylinder or make a cylinder a part of an electrical circuit. Do not smoke while handling product or cylinders. Never re-compress a gas or a gas mixture without first consulting the supplier. Never attempt to transfer gases from one cylinder/container to another. Always use backflow protective device in piping. Never use direct flame or electrical heating devices to raise the pressure of a container. Containers should not be subjected to temperatures above 50°C. Prolonged periods of cold temperature below -30°C should be avoided.

Storage

Full containers should be stored so that oldest stock is used first. Containers should be stored in a purpose built compound which should be well ventilated, preferably in the open air. Stored containers should be periodically checked for general condition and leakage. Observe all regulations and local requirements regarding storage of containers. Protect containers stored in the open against rusting and extremes of weather. Containers should not be stored in conditions likely to encourage corrosion. Containers should be stored in the vertical position and properly secured to prevent toppling. The container valves should be tightly closed and where appropriate valve outlets should be capped or plugged. Container valve guards or caps should be in place. Keep containers tightly closed in a cool, well-ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Full and empty cylinders should be segregated. Do not allow storage temperature to exceed 50°C. Return empty containers in a timely manner.







www.pyroguard.co.za

www.deleifire.com

GASES DATA SHEET: NITROGEN GENERAL INDUSTRIAL DATA SHEET

Technical measures/Precautions

Containers should be segregated in the storage area according to the various categories (e.g. flammable, toxic, etc.) and in accordance with local regulations. Keep away from combustible material.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures

Provide natural or mechanical ventilation to prevent oxygen deficient atmospheres below 19.5% oxygen.

Personal	protective	eaui	oment
. c.so.ia.	PIOCECCIAC	Cqu.	D111C11C

Respiratory protection	Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmosphere. Air purifying respirators will not provide protection. Users of breathing apparatus must be trained.
Hand protection	Sturdy work gloves are recommended for handling cylinders. The breakthrough time of the selected glove(s) must be greater than the intended use period.
Eye protection	Safety glasses recommended when handling cylinders.
Skin and body protection	Safety shoes are recommended when handling cylinders.
Special instructions for protection and hygiene	Ensure adequate ventilation, especially in confined areas.
Remarks	Simple asphyxiant.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	Compressed gas.
Color	Colorless gas
Odor	No odor warning properties.
Molecular Weight	28 g/mol
Relative vapor density	0.97 (air = 1)
Vapor pressure	Not applicable.
Density	0.0012 g/cm ³ at 21 °C Note: (as vapor)
Specific Volume	0.8615 m³/kg at 21 °C
Boiling point/range	-196 °C
Critical temperature	-147 °C
Melting point/range	-210 °C
Water solubility	0.02 g/l
40. OTA DILITY AND DEACTIVITY	

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Hazardous decomposition products	None.

11. TOXICOLOGICAL INFORMATION

Acute Health Hazard

Ingestion	No data is available on the product itself.
Inhalation	No data is available on the product itself.
Skin	No data is available on the product itself.







www.pyroguard.co.za

www.deleifire.com

GASES DATA SHEET: NITROGEN GENERAL INDUSTRIAL DATA SHEET

Ecotoxicity effects	
Aquatic toxicity	No data is available on the product itself.
Toxicity to other organisms	No data available.
Persistence and degradability	
Mobility	No data available.
Bioaccumulation	No data is available on the product itself.
Further information	
No ecological damage caused by this pro	duct.
13. DISPOSAL CONSIDERATIONS	
Waste from residues / unused products	Contact supplier if guidance is required. Return unused product in original cylinder to supplier.
Contaminated packaging	Return cylinder to supplier.
14. TRANSPORT INFORMATION	
ADR	
Proper shipping name	NITROGEN, COMPRESSED
Class	2.2
UN/ID No.	UN1066
Class	2
ADR/RID Hazard ID no.	20
IATA	
Proper shipping name	Nitrogen, compressed
Class	2.2
UN/ID No.	UN1066
IMDG	
Proper shipping name	NITROGEN, COMPRESSED
Class	2.2
UN/ID No.	UN1066
RID	
Proper shipping name	NITROGEN, COMPRESSED
Class	2.2
UN/ID No.	UN1066

Further Information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. The transportation information is not intended to convey all specific regulatory data relating to this material. For complete transportation information, contact an Air Products customer service representative.







www.pyroguard.co.za

www.deleifire.com

GASES DATA SHEET: NITROGEN GENERAL INDUSTRIAL DATA SHEET

15. REGULATORY INFORMATION		
OHS Act	Occupational Health and Safety Act 85 of 1993 (and Regulations)	
SANS 10265	The classification and labelling of dangerous substances and preparations for sale and handling	
SANS 10019	Transportable containers for compressed, dissolved and liquefied gases – Basic design, manufacture, use and maintenance	
SANS 1518	Transport of dangerous goods – Design, construction, testing, approval and maintenance of road vehicles and portable tanks	
SANS 10228	The identification and classification of dangerous goods for transport	
SANS 10229-1 & 2	Transport of dangerous goods – Packaging and large packaging for road and rail transport Part 1: Packaging / Part 2: Large Packaging	
SANS 10263-2	The warehousing of dangerous goods Part 2: The storage and handling of gas cylinders	
NB: Refer to latest edition		
16. OTHER INFORMATION		
R-phrase(s)	Not a hazardous substance in accordance with SANS 10265:1999	
Ensure all national/local regulations are	observed.	
_	ed to be correct at the time of going to press. Whilst proper care has been taken in the or for injury or damage resulting from its use can be accepted.	
(Reference www.airproducts.com :- Air Products PLC Nitrogen		
MSDS Number 30000000099 / Version 1.12 / Revision Date 11.05.2008)		