



HOSE REEL FRAME



Product code: K001.1

Fixed Type Fire Hose Reel Frame



Product code: K001.2

Fixed Type Green Hose Reel Frame

Code	Component	Description	Qty
K022	Front & Back Plate	570mm diameter, 1mm mild steel disc forged, phosphated & finished in a epoxy powder coating	2
K025	Hub Spacers	160mm wide cadmium plated curved spacer	3
	Bolts & Nuts & Washers for Spacers	M8 x 12 plated hex bolt & nut with M8 Bright nickel plated washer	12
K021	Back Plate Bush	White nylon bush / grommet with 25mm ID	1
	Bolts & Nuts for Nylon Bush	M4 x 10 plated cheese head screw & hex nut	3
K013	Waterway	Brass swivel joint with cadmium plated goose neck	1
K0011.1	Back Frame – Bottom Mounting Holes	Mild steel back frame with bottom mounting holes, 360mm spacing between holes	
K0011.1	Back Frame – Top Mounting Holes	Mild steel back frame with top mounting holes, 230mm spacing between holes	1
K0011.1	Back Frame – Stand Pipe	25mm threaded mild steel pipe phosphated & finished in a epoxy powder coating	
K015	Draw Shackle	Mild steel nickel plated shackle with PVC run out guide	1
K018.2	Instruction Label	Printed Pyroguard instruction label	1

Weight of Hose Reel Frame	7.45kg
Total Dimensions of Hose Reel in Carton Box	660mm x 580mm x 250mm (W x D x H)
SABS Permit No.	MRK 9068 / 14366
SABS Specification No.	SANS 543

Warranty Conditions That Apply: All new fire hose reels supplied carry a twelve month warranty against defective workmanship and hose from the date of delivery. Providing such equipment is installed correctly and used for the intended design purpose. The warranty excludes unauthorised use, incorrect installation, or corrosion due to electrical and chemical influences.



HOSE REELS COMPLETE



Product code: K004.1

Fixed Type Fire Hose Reel Complete with Red PVC Hose & Aluminium Nozzle

Product code: K004.2

Fixed Type Fire Hose Reel Complete with Red PVC Hose & Plastic Nozzle



Product code: K003

Fixed Type Green Hose Reel Complete with Black PVC Hose & Aluminium Nozzle

Product code: K004

Fixed Type Green Hose Reel Complete with Black PVC Hose & Plastic Nozzle

Component	Description
Std Hose Length & Diameter	30metres PVC x 20mm Diameter
Hose Specification	SANS 1086 & EN694
Nominal Inside Diameter of Hose	19mm
Working Pressure for Hose Reel in kPa	1200 kPa
Test Pressure for Hose Reel in kPa	1800 kPa
Minimum Burst Pressure for Hose Reel in kPa	3000 kPa
Discharge Rate (std 300kPa)	30L/min @300kPa
Effective Throw Range for Jet Discharge @ 0.2 MPa	10m for jet spray
Effective Throw Range for Sheet Spray Discharge @ 0.2 MPa	6m for sheet spray
Effective Throw Range for Conical Spray Discharge @ 0.2 MPa	3m for conical spray
Nozzle Type	19mm Red Plastic, light alloy & black nylon nozzle with spray, jet & shut-off function
Valve	Chromium plated stock cock with 25mm BSP inlet & outlet
Total Mass with Hose	18.2kg
Total Dimensions of Hose Reel in Carton Box	660mm x 580mm x 250mm (W x D x H)
SABS Specification No.	SANS 543
SABS Permit No.	MRK 9068 / 14366

Warranty Conditions That Apply: All new fire hose reels supplied carry a twelve month warranty against defective workmanship and hose from the date of delivery. Providing such equipment is installed correctly and used for the intended design purpose. The warranty excludes unauthorised use, incorrect installation, or corrosion due to electrical and chemical influences.