



FIRE HOSE NOZZLES AND BRANCH PIPES

Product Code	Component	Description	
P016.1	Branch Pipe – Mini Jet Spray Nozzle With 19mm Tail Insert	<ul style="list-style-type: none"> • Plastic nozzle/ light alloy • Hose tail diameter size: 19mm • Diameter of outlet: 4.0mm • Weight: 0.35Kg 	
P016.4	Branch Pipe – Mini Jet Spray Nozzle With 25mm Tail Insert	<ul style="list-style-type: none"> • Plastic / light alloy nozzle • Hose tail diameter size: 25mm • Diameter of outlet: 4.0mm • Weight: 0.35Kg 	
P015	Branch Pipe – Jet Spray Nozzle with 16mm Shut-off Valve	<ul style="list-style-type: none"> • Light Alloy nozzle • Diameter of outlet: 16mm • Coupling fitting: 65mm John Morris • Function: Jet, spray with shut-off • Jet Flow Rate @ 3.6bar: Jet ≥ 249L/minute x Discharge Range: >20m • Spray Flow Rate @ 3.6bar: Jet ≥ 252L/minute x Discharge Range: >11m • Weight: 2.05Kg 	
P016	Branch Pipe – Jet Spray Nozzle with 9mm Shut-off Valve	<ul style="list-style-type: none"> • Light Alloy nozzle • Diameter of outlet: 9mm • Coupling fitting: 65mm John Morris • Function: Jet, spray with shut-off • Jet Flow Rate @ 6.9bar: Jet ≥ 130L/minute x Discharge Range: >21m • Spray Flow Rate @ 6.9bar: Jet ≥ 132L/minute x Discharge Range: >14m • Weight: 1.15Kg 	
P016.2	Branch Pipe – Jet Spray Nozzle with 9mm Multi-Function Curtain Spray	<ul style="list-style-type: none"> • Light Alloy nozzle • Diameter of outlet: 9mm • Coupling fitting: 65mm John Morris • Function: Jet, spray, curtain spray with shut-off • Jet Flow Rate @ 6.9bar: Jet ≥ 130L/minute x Discharge Range: >21m • Spray Flow Rate @ 6.9bar: Jet ≥ 132L/minute x Discharge Range: >14m • Weight: 2.05Kg 	
P016.3	Branch Pipe – Jet Spray Nozzle with 16mm Multi-Function Curtain Spray	<ul style="list-style-type: none"> • Light Alloy nozzle • Diameter of outlet: 16mm • Coupling fitting: 65mm John Morris • Function: Jet, spray, curtain spray with shut-off • Jet Flow Rate @ 3.6bar: Jet >249L/minute x Discharge Range: >20m • Spray Flow Rate @ 3.6bar: Jet >252L/minute x Discharge Range: >11m • Weight: 1.55Kg 	
P014	Branch Pipe – Straight Through Nozzle	<ul style="list-style-type: none"> • Light Alloy nozzle • Diameter of outlet: 16mm / 13mm • Coupling fitting: 65mm John Morris • Function: Jet • Weight: 0.75Kg 	

LAY FLAT HOSES

Product Code	Component	Diameter Hose	Hose Length	Material Outside	Material Inside	Working Pressure	Burst Pressure	Packing Weight	Package Size (mm) L x W x H
P029	White Canvas Hose Complete with Couplings – Single PVC Lined 13bar	40mm	30meter	White synthetic fibre polyester single jacket	PVC	13bar	39bar	5.15Kg	440 x 370 x 90
P030	White Canvas Hose Complete with Couplings – Single PVC Lined 13bar	65mm	30meter	White synthetic fibre polyester single jacket	PVC	13bar	39bar	9.30Kg	460 x 360 x 120
<p>Features</p> <ul style="list-style-type: none"> • Non-percolating, light weight, all synthetic hose • Is designed for fire-fighting application or water discharge • Operating temperature range: -20°C to 60°C based on water • Constructed from close woven polyester filament yarns with synthetic PVC inner lining • Complete with light alloy couplings 									



Product Code	Component	Diameter Hose	Hose Length	Material Outside	Material Inside	Working Pressure	Burst Pressure	Packing Weight	Package Size (mm) L x W x H
P027.1	Pyrocheck Red Double Lined Hose Complete with Couplings –13bar	40mm	30meter	PVC	PVC	13bar	39bar	7.75Kg	550 x 350 x 90
P028.1	Pyrocheck Red Double Lined Hose Complete with Couplings –13bar	65mm	30meter	PVC	PVC	13bar	39bar	12.10Kg	500 x 420 x 130
<p>Features</p> <ul style="list-style-type: none"> • Red in colour, non-percolating, light weight, all synthetic, durable fire hose • Is designed for fire-fighting application • Operating temperature range: -20°C to 60°C based on water • Constructed from close woven polyester filament yarns with synthetic PVC inner and outer lining for extra abrasion resistance • The PVC coating gives protection and increase the resistance to chemicals and oil and increases the life of the hose • Complete with light alloy couplings 									



Product Code	Component	Diameter Hose	Hose Length	Material Outside	Material Inside	Working Pressure	Burst Pressure	Packing Weight	Package Size (mm) L x W x H
P040.1	Pyrocheck Blue Double Lined Hose Complete with Couplings –16bar	40mm	30meter	PVC	PVC	16bar	48bar	9.10Kg	620 x 520 x 100
P028.3	Pyrocheck Blue Double Lined Hose Complete with Couplings –16bar	65mm	30meter	PVC	PVC	16bar	48bar	14.05Kg	550 x 470 x 130
<p>Features</p> <ul style="list-style-type: none"> • Blue in colour, non-percolating, light weight, all synthetic, durable fire hose • Is designed for fire-fighting application and industrial wash down • Operating temperature range: -20°C to 60°C based on water • Constructed from close woven polyester filament yarns with synthetic PVC inner and outer lining for extra abrasion resistance • The PVC coating gives protection and increase the resistance to chemicals and oil and increases the life of the hose • Complete with light alloy couplings 									

